

SAFETY JOGGER

INDUSTRIAL

SPORTS

MORRIS S1P

The most responsible safety shoe with ultimate comfort

Each pair contains 10 to 12 plastic bottles worth of ocean waste. Making the Morris one of the most eco-friendly safety shoe available. The upper knitwear is made of recycled materials. The well known Ortholite removable footbed is made of recycled rubber. On top of that, we guarantee the above standard comfort and protection.

Upper	Knitted Recycled Textile, Recycled Microfibre
Outsole	EVA/Rubber
Toecap	Nano Carbon
Midsole	Nonwoven
Lining	Mesh
Footbed	Comfort Footbed
Standards	S1P / ESD, SRC
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 / CM 23.5-31.0



BLK



SRC
Slip resistant soles are one of the most vital elements in safety footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



SJ FOAM
The SJ Foam footbed combines extra comfortable heel and arch support with air breathability. They are designed to give minimal impact with the ground while offering maximum comfort.



ELECTROSTATIC DISCHARGE (ESD)
Static discharges can ignite flammable mixtures and damage electronic components. ESD footwear prevents a build-up of static electrical charges in the human body by sending them to the ground in a very safe and controlled manner.



NANO CARBON TOECAP
Carbon nanofiber material makes these shoes the lightest. It weighs 50% less than a traditional steel safety toecap and 40% less than a composite toecap. This toecap does not conduct heat or cold.

SAFETY JOGGER

INDUSTRIAL

SPORTS

MORRIS S1P

Industries:

Automotive, Construction, Logistics, Production

Environments:

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



	Description	Measure unit	Result	EN ISO 20345
Upper	Knitted Recycled Textile, Recycled Microfibre			
	Upper: permeability to water vapor	mg/cm ² /h	41.9	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	336	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	50.4	≥ 2
	Lining: water vapor coefficient	mg/cm ²	403	≥ 20
Footbed	Comfort Footbed			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	EVA/Rubber			
	Outsole abrasion resistance (volume loss)	mm ³	96.8	≤ 150
	Outsole slip resistance SRA: heel	friction	0.43	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.42	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	97.3	0.1 - 1000
	ESD value	MegaOhm	NA	0.1 - 100
	Heel energy absorption	J	22.3	≥ 20
Toecap	Nano Carbon			
	Impact resistance toecap (clearance after impact 100J)	mm	NA	≥ 14
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	≥ 14
	Impact resistance toecap (clearance after impact 200J)	mm	16.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	19.5	≥ 14

Our shoes are constantly evolving, the technical data above may change.

All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size: 42

SAFETY JOGGER
WORKS

INDUSTRIAL PROFESSIONAL TACTICAL

WWW.SAFETYJOGGER.COM

ENGINEERED
IN EUROPE